

# Table of Contents

- Switch to Legacy Interface Names** ..... 1
  - Disable new naming*** ..... 1
  - Create a new grub config*** ..... 1
  - Create persistent-net rule in udev*** ..... 1
  - Rename network scripts*** ..... 2



[centos](#), [interface](#), [network](#)

# Switch to Legacy Interface Names

## Disable new naming

Edit `/etc/default/grub`:

```
vim /etc/default/grub
```

Add **`net.ifnames=0`** at the end of **`GRUB_CMDLINE_LINUX=""`**

It should look like this:

```
GRUB_TERMINAL_OUTPUT="console"
GRUB_CMDLINE_LINUX="biosdevname=0 crashkernel=auto nomodeset rd.auto=1
consoleblank=0 nouveau.modeset=0 rd.driver.blacklist=nouveau
plymouth.ignore-udev net.ifnames=0"
GRUB_DISABLE_RECOVERY="true"
```

## Create a new grub config

```
grub2-mkconfig -o /boot/grub2/grub.cfg
```

## Create persistent-net rule in udev

Edit the file `/etc/udev/rules.d/70-persistent-net.rules` like (the file probably doesn't exist):

```
vim /etc/udev/rules.d/70-persistent-net.rules
```

and add one line per interface like this:

```
SUBSYSTEM=="net", ACTION=="add", DRIVERS=="?*",
ATTR{address}=="HH:HH:HH:HH:HH:HH", ATTR{type}=="1", KERNEL=="eth*",
NAME="eth0"
```

where `HH:HH:HH:HH:HH:HH` is the MAC Address of that interface.

## Rename network scripts

Find the interface files here **/etc/sysconfig/network-scripts** and move them to their new names, for each script you need to edit it and change the device name as in the example below.

```
mv /etc/sysconfig/network-scripts/ifcfg-en0s0p0 /etc/sysconfig/network-scripts/ifcfg-eth0
```

From:

<https://esgr.in/wiki/> - **eSGR Documentation**

Permanent link:

[https://esgr.in/wiki/systems/legacy\\_interface\\_names](https://esgr.in/wiki/systems/legacy_interface_names)

Last update: **2018/03/05 05:29**

