

Table of Contents

- Switch to Legacy Interface Names** 1
 - Disable new naming*** 1
 - Create a new grub config*** 1
 - Create persistent-net rule in udev*** 1
 - Rename network scripts*** 2

Centos

Switch to Legacy Interface Names

Disable new naming

Edit /etc/default/grub:

```
vim /etc/default/grub
```

Add **net.ifnames=0** at the end of **GRUB_CMDLINE_LINUX=""**

It should look like this:

```
GRUB_TERMINAL_OUTPUT="console"
GRUB_CMDLINE_LINUX="biosdevname=0 crashkernel=auto nomodeset rd.auto=1
consoleblank=0 nouveau.modeset=0 rd.driver.blacklist=nouveau
plymouth.ignore-udev net.ifnames=0"
GRUB_DISABLE_RECOVERY="true"
```

Create a new grub config

```
grub2-mkconfig -o /boot/grub2/grub.cfg
```

Create persistent-net rule in udev

Edit the file **/etc/udev/rules.d/70-persistent-net.rules** like (the file probably doesn't exist):

```
vim /etc/udev/rules.d/70-persistent-net.rules
```

and add one line per interface like this:

```
SUBSYSTEM=="net", ACTION=="add", DRIVERS=="?*",
ATTR{address}=="HH:HH:HH:HH:HH:HH", ATTR{type}=="1", KERNEL=="eth*",
NAME="eth0"
```

where HH:HH:HH:HH:HH:HH is the MAC Address of that interface.

Rename network scripts

Find the interface files here **/etc/sysconfig/network-scripts** and move them to their new names, for each script you need to edit it and change the device name as in the example below.

```
mv /etc/sysconfig/network-scripts/ifcfg-en0s0p0 /etc/sysconfig/network-  
scripts/ifcfg-eth0
```

From:

<https://esgr.in/wiki/> - **eSGR Documentation**

Permanent link:

https://esgr.in/wiki/systems/legacy_interface_names?rev=1515672012

Last update: **2018/01/11 12:00**

