

Table of Contents

- Create the systemd service** 1
 - Create the service file*** 1
 - service file contents*** 1
 - setup nginx.conf*** 1

Create the systemd service

Create the service file

```
vim /lib/systemd/system/nginx.service
```

service file contents

```
[Unit]
Description=The nginx HTTP and reverse proxy server
After=syslog.target network.target remote-fs.target nss-lookup.target

[Service]
Type=forking
PIDFile=/var/run/nginx/nginx.pid
# Nginx will fail to start if /var/run/nginx/nginx.pid already exists but
# has the wrong
# SELinux context. This might happen when running `nginx -t` from the
# cmdline.
# https://bugzilla.redhat.com/show_bug.cgi?id=1268621
ExecStartPre=/usr/sbin/nginx -t
ExecStart=/usr/sbin/nginx
ExecReload=/bin/kill -s HUP $MAINPID
ExecStop=/bin/kill -s QUIT $MAINPID
PrivateTmp=true

[Install]
WantedBy=multi-user.target
```

setup nginx.conf

```
pid /var/run/nginx/nginx.pid;
user nginx nginx;
```

From:
<https://esgr.in/wiki/> - **eSGR Documentation**

Permanent link:
<https://esgr.in/wiki/systems/nginx.service?rev=1516672694>

Last update: **2018/01/23 01:58**

